


T-51 2" / 51-mm


Drill Steel

	LENGTH		PART NUMBER	WEIGHT	
	FEET/INCHES	MILLIMETER		POUNDS	KILO-
 <p>Single Thread</p>	12'	3660	12ST51G	112.8	51.2
	14'	4265	14ST51G	131.6	59.7
	20'	6095	20ST51G	188.0	85.3
 <p>Male / Female</p>	12'4"	3760	12MF51G	125.3	56.8
	20'4"	6198	20MF51G	200.5	90.9





Coupling

		DIAMETER		PART NUMBER	WEIGHT	
		INCHES	MILLIMETER		POUNDS	KILO-
 <p>NO FLATS</p>		3"	76	<i>CCT5100</i>	10.5	4.7
		3"	76	51CPLBG	10.5	4.7
COMBINATION	T-45 - T-51	3"	76	45X51CPL	6.4	2.9

Rok-Bits

 <p>HI-Duty X-Design</p>	4 1/2"	115	450XB51G	13.6	6.2
	5"	127	500XB51G	15.4	7.0

Button Bits

 <p>CROWN</p>	3-1/2"	89	<i>S3551H0</i>	8.4	3.8
	4"	102	<i>S4051H0</i>	10.5	4.8
	4 1/2"	115	<i>S4551H0</i>	13.6	6.2
	5"	127	<i>S5051H0</i>	15.4	7.0
 <p>DROP CENTER</p>	3-1/2"	89	350BB51G	8.4	3.8
	4"	102	400BB51G	10.5	4.8
	4 1/2"	115	450BB51G	13.6	6.2
	5"	127	500BB51G	15.4	7.0
 <p>FLAT FACE</p>	3-1/2"	89	<i>S3551F0</i>	8.4	3.8
	4"	102	<i>S4051FA</i>	10.5	4.8
	4 1/2"	115	<i>S4551FA</i>	13.6	6.2
 <p>Retrac Button Bits</p>	3-1/2"	89	350BB51RETG	10.5	4.8
	4"	102	400BB51RETG	14.6	6.6
	4-1/2"	115	450BB51RETG	16.4	7.4
	5"	127	500BB51RETG	18.2	8.2

Straight hole available upon request.