







# 125-ROPE 1-1/4"/ 32-mm R-32

| DIAMETER |            | PART NUMBER  | WEIGHT |           | 125 Rope   | 100Rope - 125 Rope<br>125 Rope - 150 Rope<br>125 Rope - T-38   | Combination               |
|----------|------------|--------------|--------|-----------|--|--|---------------------------|
| INCHES   | MILLIMETER |              | POUNDS | KILOGRAMS |  |  |                           |
| 1 3/4"   | 45         | 125RCPLBG    | 2.0    | .9        |   |  |                           |
| 1 3/4"   | 45         | 125X100RCPL  | 2.1    | .9        |  |  |                           |
| 2 1/8"   | 54         | 150X125RCPL  | 4.2    | 2.1       |  |  |                           |
| 2 1/8"   | 54         | 38X125RCPL   | 4.2    | 2.1       |  |  |                           |
| 1 5/8"   | 41         | 163XB125RG   | 1.1    | .5        |    | <b>STANDARD<br/>4-POINT</b>  |                           |
| 1 3/4"   | 45         | 175XB125RG   | 1.2    | .6        |  |  |                           |
| 1 7/8"   | 48         | 188XB125RG   | 1.5    | .7        |  |  |                           |
| 2"       | 51         | 200XB125RG   | 1.7    | .8        |  |  |                           |
| 2 1/4"   | 57         | 225XB125RG   | 1.8    | 1.0       |  |  |                           |
| 2 1/2"   | 64         | 250XB125RG   | 2.5    | 1.1       |  |  |                           |
| 2 3/4"   | 70         | 275XB125RG   | 3.0    | 1.4       |  |  |                           |
| 3"       | 76         | 300XB125RG   | 3.5    | 1.6       |  |  |                           |
| 1 3/4"   | 45         | T1712N0      | 1.2    | .6        |   | <b>HI-DUTY<br/>4-POINT</b>   | <i>Made to order only</i> |
| 1 7/8"   | 48         | T1912N0      | 1.5    | .7        |  |  |                           |
| 2"       | 51         | T2012N0      | 1.7    | .8        |  |  |                           |
| 2 1/4"   | 57         | T2212N0      | 1.8    | 1.0       |  |  |                           |
| 1 5/8"   | 41         | S1612M       | 1.3    | .6        |  | <b>MODIFIED<br/>CHISEL</b>   |                           |
| 1 3/4"   | 45         | S1712M       | 1.5    | .7        |  |  |                           |
| 1 7/8"   | 48         | S1912M       | 1.7    | .8        |  |  |                           |
| 2"       | 51         | S2012M       | 2.0    | .9        |  |  |                           |
| 1 5/8"   | 41         | 163BB125RG   | 1.3    | .6        |  | <b>CROWN</b>   |                           |
| 1 3/4"   | 45         | 175BB125RG   | 1.5    | .7        |  |  |                           |
| 1 7/8"   | 48         | 188BB125RG   | 1.7    | .8        |  |  |                           |
| 2"       | 51         | 200BB125RG   | 2.0    | .9        |  |  |                           |
| 2 1/4"   | 57         | 225BB125RG   | 2.2    | 1.0       |  |  |                           |
| 2 1/2"   | 64         | 250BB125RG   | 2.5    | 1.1       |  |  |                           |
| 3"       | 76         | 300BB125RG   | 2.7    | 1.2       |  |  |                           |
| 2"       | 51         | 200BB125RETG | 2.0    | .9        |  | <b>Retrac Button Bits</b><br>Call our customer service<br>representatives for bit<br>and carbide type. |                           |
| 2-1/4"   | 51         | 225BB125RETG | 2.7    | 1.2       |  |  |                           |

Couplings

Rok-Bits

Button Bits

Button Bits are available with Standard, Parabolic, Ballistic, or Conical Carbide

- Parabolic = P as the last digit
- Ballistic = B as the last digit
- Conical = C as the last digit

