







150-Rope 1-1/2" / 38mm **R-38**

DIAMETER		PART NUMBER	WEIGHT		
INCHES	MILLIMETER		POUNDS	KILOGRAMS	
2-1/8"	54	150RCPLBG	3.5	1.6	150 Rope 
2-1/8"	54	150X125RCPL	4.9	2.2	125 Rope - 150 Rope COMBINATION 150 Rope - T-38
2-1/8"	54	38X150RCPL	3.7	1.7	
2 1/2"	64	<i>T2515X0</i>	3.6	1.6	STANDARD X-Design 
2 3/4"	70	<i>T2715X0</i>	4.2	1.9	
3"	76	<i>T3015X0</i>	4.8	2.2	
3 1/2"	89	<i>T3515X0</i>	6.5	2.9	
4"	102	<i>T4015X0</i>	8.7	3.9	
2 1/2"	64	250XB150RG	3.8	1.7	HI-DUTY X-Design 
2 3/4"	70	275XB150RG	4.4	2.0	
3"	76	300XB150RG	5.0	2.3	
3 1/2"	89	350XB150RG	6.8	3.1	
4"	102	400XB150RG	9.0	4.1	
2 1/2"	64	<i>S2515C0</i>	3.7	1.7	CROWN 
2 3/4"	70	<i>S2715C0</i>	4.3	1.9	
3"	76	<i>S3015H0</i>	4.7	2.1	
3 1/2"	89	<i>S3515H0</i>	5.2	2.4	
4"	102	<i>S4015H0</i>	8.4	3.8	
2 1/2"	64	250BB150RG	3.7	1.7	DROP CENTER 
2 3/4"	70	275BB150RG	4.3	1.9	
3"	76	300BB150RG	4.7	2.1	
3 1/2"	89	350BB150RG	5.2	2.4	
4"	102	400BB150RG	8.4	3.8	
2 1/2"	64	<i>S2515F0</i>	3.7	1.7	FLAT FACE 
2 3/4"	70	<i>S2715F0</i>	4.3	1.9	
3"	76	<i>S3015FA</i>	4.7	2.1	
3 1/2"	89	<i>S3515FA</i>	5.2	2.4	
4"	102	<i>S4015FA</i>	8.4	3.8	

Couplings

Rok - Bits

Button Bits

Button Bits are available with Standard, Parabolic, Ballistic, or Conical Carbide

- Parabolic = P as the last digit
- Ballistic = B as the last digit
- Conical = C as the last digit

