




T-38 1-1/2" / 38mm


Carbex

	LENGTH		PART NUMBER	WEIGHT	
	FEET/INCHES	MILLIMETER		POUNDS	KILOGRAMS
1-1/4" (32mm) Hexagon					
	10'	3050	10ST38GHEX	45.6	20.7
Single Thread	12'	3660	10ST38GHEX	54.4	24.7
	14'	4265	10ST38GHEX	59.8	27.1

Drifter Rods

1-1/4" (32mm) Hexagon					
	10' 1-1/2"	3073	10ST38ST125RG	43.5	19.7
T-38 (38mm) to 125-Rope (R32)	12' 1-1/2"	3683	12ST38ST125RG	51.8	23.5
	14' 1-1/2"	4293	14ST38ST125RG	63.6	28.8
	16' 1-1/2"	4902	16ST38ST125RG	68.0	30.8
	18' 1-1/2"	6274	18ST38ST125RG	81.3	36.9
	1-3/8" (35mm) Hexagon				
	16' 1-1/2"	4902	<i>K8193CQ</i>	85.6	38.8
T-38 (38mm) to 125-Rope (R32)	18' 1-1/2"	6274	<i>K8217CQ</i>	96.0	43.5

Round Drill Steel

1-1/2" (38mm) ROUND					
	6'	1830	06ST38G	31.4	27.8
Single Thread	8'	2440	08ST38G	41.9	19.0
	10'	3050	10ST38G	52.4	23.7
	12'	3660	12ST38G	62.8	28.4
	14'	4265	14ST38G	73.3	33.2
	16'	4875	16ST38G	83.8	38.0
	18'	5485	18ST38G	94.3	42.8
	<small>Picture shown with flats. Add an F to the end of the part number if flats are required.</small>				
1-1/2" (38mm) ROUND					
	10'	3050	10TT38G	52.4	23.7
Tandem Thread	12'	3660	12TT38G	62.8	28.4
	14'	4265	14TT38G	73.3	33.2
	16'	4875	16TT38G	83.8	38.0
	1-1/2" (38mm) ROUND				
	10'	3050	10CT38G	47.2	21.4
All Thread	12'	3660	12CT38G	56.6	25.6
	14'	4270	14CT38G	66.0	29.9
	1-1/2" (38mm) ROUND				
	4' 4"	1320	04MF38G	24.9	11.2
Male / Female	5' 4"	1626	05MF38G	30.2	13.6
	6' 4"	1930	06MF38G	35.4	16.0
	10' 4"	3150	10MF38G	56.4	25.5
	12' 4"	3760	12MF38G		30.3