



**Chicago
Pneumatic**

Rotary Hammers



CP0009A



CP0014RR

These versatile tools are both a drill and a chipping hammer. A push of the rotation release button easily and quickly converts the tool to a hammer.

Applications: The CP-0009 and CP-0014RR rotary hammers are designed for a wide variety of construction and maintenance applications such as driving or setting masonry anchors and drilling holes in concrete, bricks or rock. As a hammer, these tools can be used for chipping, scarifying, scaling and cleaning welds.

Features—All Models

- excellent power-to-weight ratio helps drill holes faster and easier than comparable electric rotary hammers
- built-in oiler provides continuous lubrication
- teasing throttle for precise control
- rotation release button converts tool to a hammer
- cushioned piston for smooth operation, long life
- "Hushed Power" muffler available to reduce noise

CP-0009A

- right-hand rotation for use with electric rotary hammer drill bits as well as traditional CP tungsten carbide steels (CP adapter is required for use with electric rotary hammer drill bits)

CP-0009A Kit (Designate CP-0009AK)

- Includes CP-0009A tool and basic accessories needed for safe and efficient operation. Carrying case has adequate space for additional accessories
Contents (includes one each):
CP-0009A Handril
C-133893 Goggles
P-137646 Pint of Airoilene Oil
R-048721 1/2" Tungsten Carbide Steel
R-137701 Metal Carrying Case

CP0009A, CP0009F, CP0014RR: 3/8"(NPTF) air inlet thread. CP0009BS, CP0009CS, CP0009ES, CP0014RRBS: 3/8" (BSP) air inlet thread. Air consumption at 90 psi: CP0009 20 cfm; CP0014 32 cfm

Catalog Number	Net Weight lb. (kg) Tool Only	Net Weight lb. (kg) Kit Complete	Overall Length in. (mm)	Type of Chuck in. (mm)	Rotation release
CP0009A*	8 (3.6)	-	14 3/4 (374.7)	3/4 round X 3 3/4 shank (19 x 95.2)	Yes
CP0009AK* (KIT)	-	22 (10)	-	3/4 round X 3 3/4 shank (19 x 95.2)	Yes
CP0009BS*	8 (3.6)	-	14 3/4 (374.7)	3/4 round X 3 3/4 shank (19 x 95.2)	Yes
CP0009BSK* (KIT)	-	-	-	3/4 round X 3 3/4 shank (19 x 95.2)	Yes
CP0009CS*	8 (3.6)	-	14 3/4 (374.7)	3/4 round X 3 3/4 shank (19 x 95.2)	No
CP0009ES*	8 (3.6)	-	14 3/4 (374.7)	Spline Drive	Yes
CP0009F*	8 (3.6)	-	14 3/4 (374.7)	Spline Drive	Yes
CP0014RR*	15 (6.8)	-	18 1/2 (469.9)	Spring 7/8 hex x 3 1/4 shank (22.2 x 82.6)	Yes
CP0014RRBS*	15 (6.8)	-	18 1/2 (469.9)	Spring 7/8 hex x 3 1/4 shank (22.2 x 82.6)	Yes

* Not available in U.S.A. ; includes muffler, BSP air inlet

* Unmuffled tools not sold in certain countries. Vontact local CP representative for details.

Rock Drills

Sinker Drills



CP0032A-1

Applications: Chicago Pneumatic Sinker Drills are the ideal tools for your drilling operations. Their streamlined design incorporates smooth contours, a side exhaust and a "flat back" that makes them easy to handle in quarry, mine and general excavating work. The design also provides a main valve and cylinder porting concept that helps maintain constant drilling speed throughout a long service life. Working parts are constantly protected with an effective lubrication system. Standard and "Hushed-Power" types are available in a range of weights and sizes to fit any requirement you might have.

Features—All Models

- forged steel housings withstand rugged use
- cushioned piston reduces shock
- multiposition throttle for easy starting of holes
- blower lever for deep hole cleaning, except CP-0022
- integral oiler provides continuous lubrication
- air inlet swivel improves maneuverability



CP0022

CP-0022 Sinker Drill

30-Pound Class—The CP-0022 provides drilling capability for holes up to 1 1/2" diameter, 6' deep. This is the ideal choice where a lightweight and powerful tool is needed in public works, utilities and drilling from scaffolding. Also the correct choice where air supply is limited. Spring retainer used for quick steel changes.

CP-0032A Sinker Drill

45-Pound Class—Choose the CP-0032A for holes up to 2" diameter and 10' deep. A top performer in its class, the CP-0032A is highly effective in general excavation work, quarry drilling, bench mining and other jobs requiring a sinker in the 45-pound class. The tool's durable "Beavertail" retainer helps it deliver increased contact and reduces collar wear.

CP-0069 Sinker Drill

55-Pound Class—The CP-0069 is suited for drilling 2-1/2" diameter holes 20' deep. The heavy-duty CP-0069 Sinker is a hard hitting tool that combines high drilling speed with excellent hole cleaning ability. Its trouble-free "Beavertail" retainer provides greater front-end durability and increased collar contact to reduce wear.

ALL MODELS: dry type; double-gripp handles; 3/4" (NPTF) swivel air inlet.

Catalog Number	Net Weight lb. (kg)	Overall Length with retainer in. (mm)	Standard Hex. Chuck Size in. (mm)
30-LB. CLASS, AIR CONSUMPTION: 56 CFM AT 90 PSI			
CP0022	28 (12.7)	19 7/8 (504.8)	7/8 X 3 1/4 (22.2 X 82.6)
45-LB. CLASS, AIR CONSUMPTION: 103 CFM AT 90 PSI			
CP0032A-.87	54 (24.5)	22 (558.8)	7/8 X 3 1/4 (22.2 X 82.6)
CP0032A-.87A	54 (24.5)	23 (584.2)	7/8 X 4 1/4 (22.2 X 107.9)
CP0032A-1	54 (24.5)	23 (584.2)	1 X 4 1/4 (25.4 X 107.9)
55-LB. CLASS, AIR CONSUMPTION: 130 CFM AT 90 PSI			
CP0069	64 (29.1)	24 1/2 (622.3)	1 X 4 1/4 (25.4 X 107.9)

prices of other sizes upon request

D & L THOMAS EQUIPMENT CORP.